

HTP CABIN PRESSURE UNIT - LIMITED PRODUCT WARRANTY

HTP has been testing and developing products for the premium off road market and will continue to develop and refine our products for the offroad market.

The manufacturer warrants that HTP Cabin Pressure units shall be free of defects in workmanship and material for a period of 12 months from the purchase date. The manufacturer will repair or replace defective product during the warranty period stated.

The manufacturer, at its sole discretion, will decide if the unit is to be covered under warranty.

This warranty is limited to, and does not extend to any components that have been damaged or rendered defective:

- (1) as a result of an accident or improper use.
- (2) substitution of parts not manufactured or sold by the Manufacturer.
- (3) modification of the product.

All labour and transport charges for removal, replacement and delivery of the product are the responsibility of the customer.

The Limited Warranty only covers products purchased from the approved dealer or retailer and does not cover previously used, salvaged, or refurbished products.

This warranty does not cover the filters. Replacement filters can be purchased from place of purchase.

Contact for customer warranty claims:

Heavy Terrain Products Pty Ltd T/A Heavy Terrain Products

037064 6370

info@heavyterrainproducts.com.au

FAN MOTOR WARRANTY

The manufacturer warrants for a period of two years or 2000 hours of use (whichever is the lesser) from the date of purchase. The manufacturer shall carry out any repairs that are reasonably necessary to correct any fault in the operation of your Cabin Pressure motor provided that such a fault is directly attributable to:

1. A defect in the workmanship or materials used in the manufacture of the part(s).
This warranty is void if the product is misused, altered, tampered with, or is installed or used in a manner that is inconsistent with written recommendations and/or installation instructions.
2. Please keep your Receipt as your proof of purchase, should you require any warranty assistance.

VOID WARRANTY

Any of the following events voids this warranty:

- A. Any non-authorized modification, repair or physical damage to the product, accidental or otherwise, not caused by a defect in material or workmanship.
- B. If the manufacturer or approved reseller determines that the product has been improperly installed, altered in any way or tampered with.
- C. The warranty does not protect against acts of God, such as direct lightning strikes, flood, earthquake and war. It also does not protect against vandalism, theft, normal-use wear and tear, abuse, damage due to low voltage disturbances, product or equipment modification or alteration.

EXCLUSIVE WARRANTY

There are no other warranties, expressed or excepted as required by law in Australia, implied, including implied warranty or condition of quality, merchantability or fitness for a particular purpose, and such implied warranties, if any, are limited in duration to the terms of this warranty.

The manufacturer expressly disclaims any liability under this warranty for any sums that exceed the retail value of the unit.

No agent or representative of the manufacturers, retailer, distributor or dealer has any express or implied authority to make any representation, promise, guarantee or warranty not stated in the Limited Product Warranty.

In no event shall the manufacturers be liable for direct, indirect, incidental, special, consequential or multiple damages arising out of the use of the product or damage to the connected equipment, regardless of the legal

theory on which such claim is based; even if advised of the possibility of such damage. The excluded damages include, but are not limited to, loss of profits, loss of savings or revenue, loss of life, injury, loss of use of the product or the connected equipment or any associated equipment, cost of capital, cost of any subsequent equipment, downtime, the claims of third parties, including customers, and damage to property.

CABIN PRESSURE FILTER CARE

The filters are designed to remove dust particles from the air drawn into the van.

Filters are recommended under normal use to be inspected at least every 6 months and replaced depending on condition.

If filters are exposed to excessive or prolonged exposure to dusty environments then more frequent inspections are recommended, such as every trip. Dust removed by compressed air is recommended. Removal of the 4 bolts on the top of your unit will give you access to the filter. Filters can be cleaned by inverting and gently knocking down on a hard surface and blown clean with compressed air. If this is done repeatedly, care should be taken, and filters replaced at the first sign of deterioration or failure. Filters should never be washed or placed in any water or cleaning fluid.

INSTALLATION

The unit must only be installed on the roof of the main body of the caravan and not on any slopes/angled sections.

The best position for installation is directly over the door entry to the caravan. Installation in the ensuite/shower will reduce efficiency.

Installation in a pop top over a cabinet will reduce efficiency.

The dustier the conditions of travel the more the filter will need to be cleaned.

Cut Out size: 315mm x 315mm

Roof thickness: 40mm-50mm

Roof Spacer: Required for roof thicknesses less than 40mm.

Wooden Internal Roof Packer: available on enquiry for cut outs that are 355x355 (standard 14 x14 Hatch cut out).

This may be required if retro fitting into an existing hatch.

1. Remove all 4 corner bolts from the top cover. Lift the top cover off the unit and take out the filter.
2. Drill an 8mm hole on the lower section of the cabin pressure unit. You must ensure that the power entry from the roof lines up with this hole.
3. Connect the wires and ensure that all connections are a waterproof seal.
 - a. Black wire is positive.
 - b. Blue wire is negative.
4. The use of waterproof foam tape is required and needs to be attached around the base of the unit.
5. Screw down firmly using the eight holes provided on the base of the unit.
6. Seal the External Cabin Pressure unit to the roof using a bead of external grade silicon.
7. Install the filter with the arrow facing downwards and attach the Cover with the 4 screws.

NOTE:

1. Minimum 4mm cable for positive and negative
2. Run the wires to a switch to turn the cabin unit on & off.
3. Connect to battery with an inline 20 amp fuse.
- 4.

For any further assistance please contact us on 03 7064 6370

ADDITIONAL PRODUCTS TO ASSIST WITH DUST REDUCTION IN YOUR VAN ARE OUR AUSTRALIAN MADE AND DESIGNED DUST DEFLECTORS FOR FRIDGE AND DOOR VENTS. PLEASE REFER TO OUR WEBSITE FOR MORE INFORMATION.

www.heavyterrainproducts.com.au